

Sat-IF-Distribution - Multitap

5 Line Multitap 1 way / 2 way

DST 55-01 1 way 12 dB
 DST 55-11 1 way 12...25dB

- 5-Line Multitap 1 way for 4 Sat + terr. input
- robust die cast frame
- Attenuator Sat / terr. - option
- small compact size
- Option: with attenuator 12...25 dB
- high isolation between polarisations
- return loss < 10 dB (low bit errors)
- F-pitch compatible to splitter/taps, amplifier and dcsc switches
- Made in Germany



Type		DST 55-01		DST 55-11	
Feature		1 / 2 way multitap, passive			
		Terr.	Sat	Terr.	Sat
Inputs		1 x terr.	4 x Sat	1 x terr.	4 x Sat
Outputs tap		1 x terr.	4 x Sat	2 x terr.	2 x (4x Sat)
Frequency range	MHz	5-862*	950-2200	5-862*	950-2200
Tap loss	dB	12	13	12	15...12*
Through loss line	dB	1,5	3	1,5	3
Attenuation optional	dB	15	15	15	15
Isolation polarisations	dB	-	30	-	30
Attenuation (option)	dB	-	15	-	15
Current consumption tap	mA	< 10		< 10	
Max. remote current	A	2			
Optional remote power	V	12...20			
Ambient temperature range	°C	-20 bis +55			
Dimensions	mm	136 x 136 x 36		136 x 136 x 36	
Weight	g	400		400	
* Band start...end					